

DIELECTRIC RIGIDITY TEST EQUIPMENT



HGN 333-B

Very small

Test voltage	0 ÷ 4	KVeff
Threshold current	2, 4, 8, 12	mA
Voltage indicator	3 ½	digit
Timer (on-off)		Yes
Test time	1 ÷ 30	sec.
Remote control		Yes
Buzzer		Option
Autostart		Option



HGN 334-BS

General purpose

Test voltage	0 ÷ 4	KVeff
Threshold current	2, 4, 8, 12	mA
Voltage indicator	3 ½	digit
Timer (on-off)		Yes
Test time	1 ÷ 198	sec.
Buzzer		Yes
Remote control		Yes
Autostart		Option



HGN 334-D

Very high current

Test voltage	0 ÷ 4	KVeff
Threshold current	12, 24, 48, 96	mA
Voltage indicator	3 ½	digit
Timer (on-off)		Yes
Test time	1 ÷ 30	sec.
Remote control		Yes
Power transformer	500	Watt
Buzzer		Yes
Autostart		Option



HGN 334-G

Very high voltage

Test voltage	0 ÷ 8 / 10	KVeff
Threshold current	6, 12, 24, 36	mA
Voltage indicator	3 ½	digit
Timer (on-off)		Yes
Test time	2 ÷ 60	sec.
Remote control		Yes
Power transformer	250	Watt
Buzzer		Yes



HGN 334-F

With current measure

Test voltage	0 ÷ 5	KVeff
Threshold current	2, 4, 8, 16	mA
Voltage indicator	3 ½	digit
Timer (on-off)		Yes
Test time	1 ÷ 30	sec.
Remote control		Yes
Buzzer		Yes
Current measure	0 ÷ 20	mA



HGN 3341

Very high current and memory discharge Voltage

Test voltage	0 ÷ 5	KVeff
Threshold current	12 ÷ 96	mA
Voltage indicator	3 ½	digit
Current indicator	3 ½	digit
Current measure	0 – 100	mA
Discharge indicator		Yes
Power transformer	500	Watt

OTHER TYPES ON REQUEST



A3 ELETTRONICA s.r.l.
Via G. Galilei, 7
Tel./Fax (+39) 02-99045633

www.a3elettronica.it
20037 Paderno Dugnano (MI) - Italy
e-mail: info@a3elettronica.it